### Risk Assessment in Hydrology and Hydraulics







Lessons Learned from the Analysis of the El Aguacate River, Guatemala





#### **Presentation Overview**

- Project Background
- Hydrologic and Hydraulic Risk Assessment Techniques
- Project Photos





### **Objectives:**

 Summarize the application of three techniques used in the hydrologic and hydraulic risk assessment of a rural bridge design.

 Show how these techniques are applicable to many H&H projects.





- Bridge Replacement,
   Aguacate Guatemala
- Engineers Without Borders (EWB), WI Professional Partners





### **Project Background**



- Existing Bridge Built 1987
- Concrete T Beam
- 32' Span



### **Project Background**

GRaEF

Structural Analysis
 Indicates Design is
 Inadequate – Low
 Quality Concrete





### **Project Background**

Shallow Abutments – No Footings







# Hydrologic and Hydraulic Risk Assessment



#### **QUESTIONS**

- Is Existing Bridge Site the Best Location?
- Is Existing Bridge Geometry Safe?
  - Span
  - Height
  - Configuration



# Hydrologic and Hydraulic Risk Assessment



#### **CHALLENGES**

- Limited Data
- Communication
- Low Budget





# Hydrologic and Hydraulic Risk Assessment



#### **APPROACH**

- Calibration of Model to Field Observations
- Iterative Approach Between
   Hydrology and Hydraulics Models
- Testing Catastrophic Scenarios –
   What If?





### **Model Calibration**



### **Options**

- -Stream Gauge Data
- -Historic flood data
- -Field Evidence



# GR

## El Aguacate Model Calibration

- No Existing Models
- No Stream Gauge Data
- No Historical Flood Data
- Villagers indicate bridge has not overtopped
- Water surface has reached bridge low chord

# Hydrologic and Hydraulic Analysis



- Hydrologic Modeling Approach TR-55
- Rainfall Data (INSIVUMEH)
  - 10-yr/24-hour 4.65 in
  - 50-yr/24-hour 5.98 in
  - 100-yr/24-hour 6.57 in





### El Aguacate Watershed




- -1225 Acres (10 M topography)
- Predominantly Woods and Grass Combination (Aerial photography)



### El Aguacate Watershed





## Hydrologic and Hydraulic Analysis



- Hydraulic Modeling Approach HEC RAS
- Assumed negligent stream base flow; used flow directly from Hydrologic Analysis
- Cross section geometry field survey
  - 6 stream cross sections
  - Bridge geometry and road profile
- Stream characteristics site photos

### **Stream Characterstics**








### **Stream Cross Sections**





### **Model Calibration**



Try to match field observation

 Model indicates water surface is more 6 feet below bridge low chord for 100 year

Increase Mannings n

Modified flow (2,900 cfs)



## Hydrology/Hydraulics Iteration



Test Hydrologic Model using Hydraulic Results

- Test Surface Conditions
- Time of Concentration
- Watershed Area
- Rainfall Depths







Tried to produce flow in Hydrology Model

- Adjusted surface conditions
- Adjusted drainage area
- Adjusted rainfall depths
- Model indicates:
  - 100% impervious doesn't produce flow
  - Rainfall Depth = 14.7 inches
  - Watershed area increased 3.5 times

### Catastrophic Scenarios – What If?



- Special Geographic Conditions / Stream Debris
  - Climate
  - Topography
  - Channel Characteristics
- Bridge Overtopping



### El Aguacate Catastrophic Scenarios




Design bridge opening to pass debris

 Special Geographic Conditions – mudslides produce "Dam Break" effects







### El Aguacate Catastrophic Scenarios



 Design roadway approach to prevent bridge overtopping

Emergency Planning – Bridge/Road Closure
 Plan

### **Bridge/Road Closure Plan**



### Risk Assessment Lessons Learned



- Revise assessment approach as necessary
- Collaborate during assessment / Subject assessment to scrutiny – peer review



TAKING RISK

There's a fine line between taking a calculated risk and doing something dumb.



### **Project Photos**





















