

Recycling Construction Demolition Debris for Stormwater Management

**BMP Case Studies:
South Shore High School Demolition
& Rosenblum Park**

**Presented by:
Nicholas Smith, PE, CFM, CPESC**




Objective

- **Recycling Concrete Aggregate (RCA)**
for stormwater management
 - Sustainable
 - Cost Effective
 - Maximizes Usable Land
 - Fine Particle Deposits
 - Sedimentation Considerations

Location

- **South Shore Neighborhood of Chicago**
- **Loose to Medium Dense Brown Sand**
- **Infiltration Rate: 2.5 in/hr**



Project Background

Site:

**South Shore
High School**

Building Footprint:

50,000 sq.ft.

Concrete Debris Estimate:


20,000 cu.yd.




Project Background

- **Client - Public Building Commission of Chicago**
- **Permitting Agency - City of Chicago DWM**
- **Demolition Budget - \$3.5 Million**
- **Construction Costs - \$2.5 Million**
- **Improvements Area - 9.7 acres**
- **Required Detention - 1.5 acre-ft**
- **Storage Provided - 2.5 acre-ft**

2008



2010



Traditional Building Demolition

- Salvage
- Recycle
- Bury
- Landfill
- CCDD




CCDD

- **Clean Construction or Demolition Debris revisions**
- **Resulting in high export cost**
- **Critical to balance the concrete and earthwork**



Detention in Stone

- Utilized a void ratio of 38% for CA-1
- Validated by field tests




Recycled Concrete Aggregate

- Reduces the need for gravel mining
- Reduces hauling costs
- Reduce the concrete debris to CCDD
- On-site Crushing and Screening equipment becoming more common
- Versatile enough to be substituted for many virgin stone applications
- Cost effective at 2,000 cu.yd.

Complications of using RCA


- Leaching results in high pH
- Fine particles are self-cementing




Infiltration Basin




Infiltration Basin Design




Basin Drainage Design




Basin Drainage Design




Basin Drainage Design




Basin Drainage Design




Basin Drainage Design




Basin Drainage Design




Basin Drainage Design




Basin Drainage Design




Basin Drainage Design




Basin Drainage Design




Basin Drainage Design




Basin Drainage Design




Basin Drainage Design




Basin Drainage Design




Basin Drainage Design



Basin Drainage Design



Basin Drainage Design



Abatement



Demolition



Demolition



Recycle



Excavation



Excavation



On-Site Crushing and Screening



On-Site Crushing and Screening



Backfill and Compaction



Backfill and Compaction



Stormwater Distribution



Compact and Cover



Park Improvements



Park Improvements



Park Improvements



Conclusion

- **RCA reduces the concrete debris to CCDD facilities and hauling costs**
- **As stormwater management it will maximize usable land**
- **Design considerations must be made for fine particle deposits and sedimentation**

References

- <http://www.epa.state.il.us/land/ccdd/index.html>
- <http://www.fhwa.dot.gov/legsregs/directives/policy/recmatpolicy.htm>
- <http://www.concreterecycling.org/>
- Arm, M. Self-cementing properties of crushed demolished concrete in unbound layers: results from triaxial tests and field tests. *Waste Management* 21 (2001), p.235-239.
- Poon, C., et al. The cause and influence of self-cementing properties of fine recycled concrete aggregates on the properties of unbound sub-base. *Waste Management* 26 (2006), p1166-1172.
- Engelsen, C., et al. Field site leaching from recycled concrete aggregates applied as sub-base material in road construction. *Science of the Total Environment* (2012), p.86-97.

Questions

Contact:

Nicholas Smith, PE, CFM, CPESC

nsmith@primerachicago.com



Primera

1 9 8 7 - 2 0 1 2

25
YEARS